

Product Features



Characteristic: They have an unique ball locking mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature -60°C ~ 550°C ;

All length are available stainless steel type:304,316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTA-3.5×100	100(3.9)	3.5(0.14)	0.25	25(1.00)	600(135)	100
LPINZ-SSCTA-3.5×150	150(5.9)		0.25	37(1.46)		100
LPINZ-SSCTA-3.5×200	200(7.87)		0.25	50(1.97)		100
LPINZ-SSCTA-3.5×250	250(9.84)		0.25	63(2.48)		100
LPINZ-SSCTA-3.5×300	300(11.8)		0.25	76(2.99)		100
LPINZ-SSCTA-3.5×350	350(13.78)		0.25	89(3.5)		100
LPINZ-SSCTA-3.5×400	400(15.75)		0.25	102(4.02)		100
LPINZ-SSCTA-3.5×450	450(17.72)		0.25	115(4.53)		100
LPINZ-SSCTA-4.6×150	150(5.9)	4.6(0.18)	0.25	37(1.46)	800(180)	100
LPINZ-SSCTA-4.6×200	200(7.87)		0.25	50(1.97)		100
LPINZ-SSCTA-4.6×250	250(9.84)		0.25	63(2.48)		100
LPINZ-SSCTA-4.6×300	300(11.8)		0.25	76(2.99)		100
LPINZ-SSCTA-4.6×350	350(13.78)		0.25	89(3.5)		100
LPINZ-SSCTA-4.6×400	400(15.75)		0.25	102(4.02)		100
LPINZ-SSCTA-4.6×450	450(17.72)		0.25	115(4.53)		100
LPINZ-SSCTA-4.6×500	500(19.69)		0.25	128(5.04)		100
LPINZ-SSCTA-4.6×550	550(21.65)		0.25	141(5.15)		100
LPINZ-SSCTA-4.6×600	600(23.62)		0.25	154(6.06)		100
LPINZ-SSCTA-7.9×150	150(5.9)	7.9(0.311)	0.25	37(1.46)	1000(225)	100
LPINZ-SSCTA-7.9×200	200(7.87)		0.25	50(1.97)		100
LPINZ-SSCTA-7.9×250	250(9.84)		0.25	63(2.48)		100
LPINZ-SSCTA-7.9×300	300(11.8)		0.25	76(2.99)		100
LPINZ-SSCTA-7.9×350	350(13.78)		0.25	89(3.5)		100
LPINZ-SSCTA-7.9×400	400(15.75)		0.25	102(4.02)		100

Product Features



Characteristic: They have an unique ball locking mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature -60°C ~ 550°C ;

All length are available stainless steel type:304,316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTA-7.9x450	600(23.62)	12(0.472)	0.4	154(6.06)	1200(270)	100
LPINZ-SSCTA-7.9x500	650(25.59)		0.4	167(6.57)		100
LPINZ-SSCTA-7.9x550	700(27.56)		0.4	180(7.09)		100
LPINZ-SSCTA-7.9x600	200(7.87)	15(0.59)	0.4	50(1.97)	1500(337)	100
LPINZ-SSCTA-7.9x650	250(9.84)		0.4	63(2.48)		100
SLPINZ-SCTA-7.9x700	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTA-7.9x750	350(13.78)		0.4	89(3.51)		100
LPINZ-SSCTA-7.9x800	400(15.75)		0.4	102(4.021)		100
LPINZ-SSCTA-10x200	450(17.72)		0.4	115(4.53)		100
LPINZ-SSCTA-10x300	500(19.69)		0.4	128(5.04)		100
LPINZ-SSCTA-10x400	550(21.65)		0.4	141(5.55)		100
LPINZ-SSCTA-10x500	600(23.62)		0.4	154(6.06)		100
LPINZ-SSCTA-10x1000	650(25.59)		0.4	167(6.57)		100
LPINZ-SSCTA-10x1200	700(27.56)		0.4	180(7.09)		100
LPINZ-SSCTA-12x150	750(29.53)		0.4	191(7.52)		100
LPINZ-SSCTA-12x200	800(31.5)		0.4	193(7.59)		100
LPINZ-SSCTA-12x250	1000(39.37)		0.4	206(8.11)		100
LPINZ-SSCTA-12x300	800(31.5)	19(0.748)	0.6	223(8.781)	1500(337)	100
LPINZ-SSCTA-12x350	1000(39.37)		0.6	286(11.26)		100
LPINZ-SSCTA-12x400	1200(47.24)		0.6	350(13.78)		100
LPINZ-SSCTA-12x450	1 500(59.04)		0.6	445(17.52)		100
LPINZ-SSCTA-12x500	1800(70.87)		0.6	540(21.26)		100
LPINZ-SSCTA-12x550	2000(78.74)		0.6	605(23.82)		100



Product Features

Characteristic: They have an unique ball locking mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature -60°C~550°C;

All length are available stainless steel type:304,316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTA-12 x 600	450(17.72)	7.9(0.311)	0.25	115(4.53)	800(180)	100
LPINZ-SSCTA-12 x 650	500(19.69)		0.25	128(5.04)		100
LPINZ-SSCTA-12 x 700	550(21.65)		0.25	141(5.55)		100
LPINZ-SSCTA-15 x 200	600(23.62)		0.25	154(6.06)		100
LPINZ-SSCTA-15 x 250	650(25.59)		0.25	167(6.57)		100
LPINZ-SSCTA-15 x 300	700(27.56)		0.25	180(7.09)		100
LPINZ-SSCTA-15 x 350	750(29.53)		0.25	191(7.52)		100
LPINZ-SSCTA-15 x 400	800(31.5)		0.25	193(7.59)		100
LPINZ-SSCTA-15 x 450	200(7.87)		0.25	50(1.97)	1000(225)	100
LPINZ-SSCTA-15 x 500	300(11.8)	10(0.394)	0.25	76(2.99)		100
LPINZ-SSCTA-15 x 550	400(15.75)		0.25	102(4.02)		100
LPINZ-SSCTA-15 x 600	500(19.69)		0.25	128(5.04)		100
LPINZ-SSCTA-15 x 650	1000(39.37)		0.25	286(11.11)		100
LPINZ-SSCTA-15 x 700	1200(47.24)		0.25	350(13.7)		100
LPINZ-SSCTA-15 x 750	150(5.9)	12(0.472)	0.25	3/(1.46)	1200(270)	100
LPINZ-SSCTA-15 x 800	200(7.87)		0.25	50(1.97)		100
LPINZ-SSCTA-15 x 1000	250(9.84)		0.25	63(2.48)		100
LPINZ-SSCTA-19 x 800	300(11.8)		0.25	76(2.99)		100
LPINZ-SSCTA-19 x 1000	350(13.78)		0.25	89(3.5)		100
LPINZ-SSCTA-19 x 1200	400(15.75)		0.25	102(4.02)		100
LPINZ-SSCTA-19 x 1500	450(17.72)		0.25	115(4.53)		100
LPINZ-SSCTA-19 x 1800	500(19.69)		0.25	128(5.04)		100
LPINZ-SSCTA-19 x 2000	550(21.65)		0.25	141(5.55)		100



Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTB-4.6×200	200(7.87)	4.6(0.181)	0.25	50(1.97)	1000(225)	100
LPINZ-SSCTB-4.6×250	250(9.84)		0.25	65(2.56)		100
LPINZ-SSCTB-4.6×350	350(13.78)		0.25	89(3.50)		100
LPINZ-SSCTB-4.6×550	550(21.65)		0.25	141 (5.55)		100
LPINZ-SSCTB-4.6×650	650(25.6)		0.25	165(6.50)		100
LPINZ-SSCTB-4.6×850	850(33.46)		0.25	216(8.50)		100
LPINZ-SSCTB-4.6×1100	1100(43.31)		0.25	280(11.02)		100
LPINZ-SSCTB-7.9×200	200(7.87)	7.9(0.311)	0.25	50(1.97)	1200(270)	100
LPINZ-SSCTB-7.9×250	250(9.84)		0.25	65(2.56)		100
LPINZ-SSCTB-7.9×350	350(13.78)		0.25	89(3.50)		100
LPINZ-SSCTB-7.9×550	550(21.65)		0.25	141(5.55)		100
LPINZ-SSCTB-7.9×650	650(25.6)		0.25	165(6.50)		100
LPINZ-SSCTB-7.9×850	850(33.46)		0.25	216(8.50)		100
LPINZ-SSCTB-7.9×1100	1100(43.31)		0.25	280(11.02)		100
LPINZ-SSCTB-7.9×150	150(5.9)	7.9(0.311)	0.25	38(1.50)	1200(270)	100
LPINZ-SSCTB-7.9×175	175(6.89)		0.25	48(1.89)		100
LPINZ-SSCTB-7.9×200	200(7.87)		0.25	52(2.05)		100
LPINZ-SSCTB-7.9×240	240(9.45)		0.25	67(2.64)		100
LPINZ-SSCTB-7.9×300	300(11.8)		0.25	82t3.23)		100
LPINZ-SSCTB-7.9×350	350(13.78)		0.25	98(8.86)		100
LPINZ-SSCTB-7.9×400	400(15.75)		0.25	114(4.49)		100
LPINZ-SSCTB-7.9×450	450(17.72)		0.25	130(5.12)		100
LPINZ-SSCTB-7.9×500	500(21.65)		0.25	146(5.75)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature $-40^{\circ}\text{C} \sim 850^{\circ}\text{C}$;

High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;

All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTC-3.5×100	100(3.9)	3.8(0.15)	0.4	25(1.00)	600(135)	100
LPINZ-SSCTC-3.5×150	150(5.9)		0.4	37(1.46)		100
LPINZ-SSCTC-3.5×200	200(7.87)		0.4	50(1.97)		100
LPINZ-SSCTC-3.5×250	250(9.84)		0.4	63(2.48)		100
LPINZ-SSCTC-3.5×300	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTC-3.5×350	350(13.78)		0.4	89(3.5)		100
LPINZ-SSCTC-3.5×400	400(15.75)		0.4	102(4.02)		100
LPINZ-SSCTC-3.5×450	450(17.72)		0.4	115(4.53)		100
LPINZ-SSCTC-4.6×150	150(5.9)	4.6(0.181)	0.4	37(1.46)	800(180)	100
LPINZ-SSCTC-4.6×200	200(7.87)		0.4	50(1.97)		100
LPINZ-SSCTC-4.6×250	250(9.84)		0.4	63(2.48)		100
LPINZ-SSCTC-4.6×300	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTC-4.6×350	350(13.78)		0.4	89(3.5)		100
LPINZ-SSCTC-4.6×400	400(15.75)		0.4	102(4.02)		100
LPINZ-SSCTC-4.6×450	450(17.72)		0.4	115(4.53)		100
LPINZ-SSCTC-4.6×500	500(19.69)		0.4	128(5.04)		100
LPINZ-SSCTC-4.6×550	550(21.65)		0.4	141(5.15)		100
LPINZ-SSCTC-4.6×600	600(23.62)		0.4	154(6.06)		100
LPINZ-SSCTC-7.9×150	150(5.9)	7.9(0.311)	0.4	37(1.46)	1000(225)	100
LPINZ-SSCTC-7.9×200	200(7.87)		0.4	50(1.97)		100
LPINZ-SSCTC-7.9×250	250(9.84)		0.4	63(2.48)		100
LPINZ-SSCTC-7.9×300	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTC-7.9×350	350(13.78)		0.4	89(3.5)		100
LPINZ-SSCTC-7.9×400	400(15.75)		0.4	102(4.02)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature $-40^{\circ}\text{C} \sim 850^{\circ}\text{C}$;

High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;

All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTC-7.9x450	450(17.72)	7.9(0.311)	0.4	115(4.53)	800(180)	100
LPINZ-SSCTC-7.9x500	500(19.69)		0.4	128(5.04)		100
LPINZ-SSCTC-7.9x550	550(21.65)		0.4	141(5.55)		100
LPINZ-SSCTC-7.9x600	600(23.62)		0.4	154(6.06)		100
LPINZ-SSCTC-7.9x650	650(25.59)		0.4	167(6.57)		100
LPINZ-SSCTC-7.9x700	700(27.56)		0.4	180(7.09)		100
LPINZ-SSCTC-7.9x750	750(29.53)		0.4	191(7.52)		100
LPINZ-SSCTC-7.9x800	800(31.5)		0.4	193(7.59)		100
LPINZ-SSCTC-10x200	200(7.87)	10(0.394)	0.4	50(1.97)	1000(225)	100
LPINZ-SSCTC-10x300	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTC-10x400	400(15.75)		0.4	102(4.02)		100
LPINZ-SSCTC-10x500	500(19.69)		0.4	128(5.04)		100
LPINZ-SSCTC-10x1000	1000(39.37)		0.4	286(11.11)		100
LPINZ-SSCTC-10x1200	1200(47.24)		0.4	350(13.7)		100
LPINZ-SSCTC-12x150	150(5.9)	12(0.472)	0.4	33(1.46)	1200(270)	100
LPINZ-SSCTC-12x200	200(7.87)		0.4	50(1.97)		100
LPINZ-SSCTC-12x250	250(9.84)		0.4	63(2.48)		100
LPINZ-SSCTC-12x300	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTC-12x350	350(13.78)		0.4	89(3.5)		100
LPINZ-SSCTC-12x400	400(15.75)		0.4	102(4.02)		100
LPINZ-SSCTC-12x450	450(17.72)		0.4	115(4.53)		100
LPINZ-SSCTC-12x500	500(19.69)		0.4	128(5.04)		100
LPINZ-SSCTC-12x550	550(21.65)		0.4	141(5.55)		100


Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;
 High tensile strength: Non-flammability;
 Temperature: Working temperature $-40^{\circ}\text{C} \sim 850^{\circ}\text{C}$;
 High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;
 All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTC-12x600	600(23.62)	12(0.472)	0.4	154(6.06)	1200(270)	100
LPINZ-SSCTC-12x650	650(25.59)		0.4	167(6.57)		100
LPINZ-SSCTC-12x700	700(27.56)		0.4	180(7.09)		100
LPINZ-SSCTC-15x200	200(7.87)	15(0.59)	0.4	50(1.97)	1500(337)	100
LPINZ-SSCTC-15x250	250(9.84)		0.4	63(2.48)		100
LPINZ-SSCTC-15x300	300(11.8)		0.4	76(2.99)		100
LPINZ-SSCTC-15x350	350(13.78)		0.4	89(3.51)		100
LPINZ-SSCTC-15x400	400(15.75)		0.4	102(4.021)		100
LPINZ-SSCTC-15x450	450(17.72)		0.4	115(4.53)		100
LPINZ-SSCTC-15x500	500(19.69)		0.4	128(5.04)		100
LPINZ-SSCTC-15x550	550(21.65)		0.4	141(5.55)		100
LPINZ-SSCTC-15x600	600(23.62)		0.4	154(6.06)		100
LPINZ-SSCTC-15x650	650(25.59)		0.4	167(6.57)		100
LPINZ-SSCTC-15x700	700(27.56)		0.4	180(7.09)		100
LPINZ-SSCTC-15x750	750(29.53)		0.4	191(7.52)		100
LPINZ-SSCTC-15x800	800(31.5)		0.4	193(7.59)		100
LPINZ-SSCTC-15x1000	1000(39.37)		0.4	206(8.11)		100
LPINZ-SSCTC-19x800	800(31.5)	19(0.748)	0.6	223(8.781)	1500(337)	100
LPINZ-SSCTC-19x1000	1000(39.37)		0.6	286(11.26)		100
LPINZ-SSCTC-19x1200	1200(47.24)		0.6	350(13.78)		100
LPINZ-SSCTC-19x1500	1500(59.04)		0.6	445(17.52)		100
LPINZ-SSCTC-19x1800	1800(70.87)		0.6	540(21.26)		100
LPINZ-SSCTC-19x2000	2000(78.74)		0.6	605(23.82)		100



Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSECT-4.6×200	200(7.87)	4.6(0.181)	0.4	50(1.97)	1000(225)	100
LPINZ-SSECT-4.6×250	250(9.84)		0.4	65(2.56)		100
LPINZ-SSECT-4.6×350	350(13.78)		0.4	89(3.50)		100
LPINZ-SSECT-4.6×550	550(21.65)		0.4	141(5.55)		100
LPINZ-SSECT-4.6×650	650(25.6)		0.4	165(6.50)		100
LPINZ-SSECT-4.6×850	850(33.46)		0.4	216(8.50)		100
LPINZ-SSECT-4.6×1100	1100(43.31)		0.4	280(11.02)		100
LPINZ-SSECT-7.9×200	200(7.87)	7.9(0.311)	0.4	50(1.97)	1200(270)	100
LPINZ-SSECT-7.9×250	250(9.84)		0.4	65(2.56)		100
LPINZ-SSECT-7.9×350	350(13.78)		0.4	89(3.50)		100
LPINZ-SSECT-7.9×550	550(21.65)		0.4	141(5.55)		100
LPINZ-SSECT-7.9×650	650(25.6)		0.4	165(6.50)		100
LPINZ-SSECT-7.9×850	850(33.46)		0.4	216(8.50)		100
LPINZ-SSECT-7.9×1100	1100(43.31)		0.4	280(11.02)		100
LPINZ-SSECT-7.9×150	150(5.9)	7.9(0.311)	0.4	38(1.50)	1200(270)	100
LPINZ-SSECT-7.9×175	175(6.89)		0.4	48(1.89)		100
LPINZ-SSECT-7.9×200	200(7.87)		0.4	52(2.05)		100
LPINZ-SSECT-7.9×240	240(9.45)		0.4	67(2.64)		100
LPINZ-SSECT-7.9×300	300(11.8)		0.4	82(3.23)		100
LPINZ-SSECT-7.9×350	350(13.78)		0.4	98(8.86)		100
LPINZ-SSECT-7.9×400	400(15.75)		0.4	114(4.49)		100
LPINZ-SSECT-7.9×450	450(17.72)		0.4	130(5.12)		100
LPINZ-SSECT-7.9×500	500(21.65)		0.4	146(5.75)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature $-40^{\circ}\text{C} \sim 850^{\circ}\text{C}$;

High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;

All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-PFSSCT-3.5×100	100(3.9)	3.8(0.15)	0.4	25(1.00)	600(135)	100
LPINZ-PFSSCT-3.5×150	150(5.9)		0.4	37(1.46)		100
LPINZ-PFSSCT-3.5×200	200(7.87)		0.4	50(1.97)		100
LPINZ-PFSSCT-3.5×250	250(9.84)		0.4	63(2.48)		100
LPINZ-PFSSCT-3.5×300	300(11.8)		0.4	76(2.99)		100
LPINZ-PFSSCT-3.5×350	350(13.78)		0.4	89(3.5)		100
LPINZ-PFSSCT-3.5×400	400(15.75)		0.4	102(4.02)		100
LPINZ-PFSSCT-3.5×450	450(17.72)		0.4	115(4.53)		100
LPINZ-PFSSCT-4.6×150	150(5.9)	4.6(0.181)	0.4	37(1.46)	800(180)	100
LPINZ-PFSSCT-4.6×200	200(7.87)		0.4	50(1.97)		100
LPINZ-PFSSCT-4.6×250	250(9.84)		0.4	63(2.48)		100
LPINZ-PFSSCT-4.6×300	300(11.8)		0.4	76(2.99)		100
LPINZ-PFSSCT-4.6×350	350(13.78)		0.4	89(3.5)		100
LPINZ-PFSSCT-4.6×400	400(15.75)		0.4	102(4.02)		100
LPINZ-PFSSCT-4.6×450	450(17.72)		0.4	115(4.53)		100
LPINZ-PFSSCT-4.6×500	500(19.69)		0.4	128(5.04)		100
LPINZ-PFSSCT-4.6×550	550(21.65)		0.4	141(5.15)		100
LPINZ-PFSSCT-4.6×600	600(23.62)		0.4	154(6.06)		100
LPINZ-PFSSCT-7.9×150	150(5.9)	7.9(0.311)	0.4	37(1.46)	1000(225)	100
LPINZ-PFSSCT-7.9×200	200(7.87)		0.4	50(1.97)		100
LPINZ-PFSSCT-7.9×250	250(9.84)		0.4	63(2.48)		100
LPINZ-PFSSCT-7.9×300	300(11.8)		0.4	76(2.99)		100
LPINZ-PFSSCT-7.9×350	350(13.78)		0.4	89(3.5)		100
LPINZ-PFSSCT-7.9×400	400(15.75)		0.4	102(4.02)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;
 High tensile strength: Non-flammability;
 Temperature: Working temperature -40°C ~ 850°C ;
 High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;
 All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-PFSSCT-7.9×450	450(17.72)	7.9(0.311)	0.4	115(4.53)	800(180)	100
LPINZ-PFSSCT-7.9×500	500(19.69)		0.4	128(5.04)		100
LPINZ-PFSSCT-7.9×550	550(21.65)		0.4	141(5.55)		100
LPINZ-PFSSCT-7.9×600	600(23.62)		0.4	154(6.06)		100
LPINZ-PFSSCT-7.9×650	650(25.59)		0.4	167(6.57)		100
LPINZ-PFSSCT-7.9×700	700(27.56)		0.4	180(7.09)		100
LPINZ-PFSSCT-7.9×750	750(29.53)		0.4	191(7.52)		100
LPINZ-PFSSCT-7.9×800	800(31.5)		0.4	193(7.59)		100
LPINZ-PFSSCT-10×200	200(7.87)	10(0.394)	0.4	50(1.97)	1000(225)	100
LPINZ-PFSSCT-10×300	300(11.8)		0.4	76(2.99)		100
LPINZ-PFSSCT-10×400	400(15.75)		0.4	102(4.02)		100
LPINZ-PFSSCT-10×500	500(19.69)		0.4	128(5.04)		100
LPINZ-PFSSCT-10×1000	1000(39.37)		0.4	286(11.11)		100
LPINZ-PFSSCT-10×1200	1200(47.24)		0.4	350(13.7)		100
LPINZ-PFSSCT-12×150	150(5.9)	12(0.472)	0.4	33(1.46)	1200(270)	100
LPINZ-PFSSCT-12×200	200(7.87)		0.4	50(1.97)		100
LPINZ-PFSSCT-12×250	250(9.84)		0.4	63(2.48)		100
LPINZ-PFSSCT-12×300	300(11.8)		0.4	76(2.99)		100
LPINZ-PFSSCT-12×350	350(13.78)		0.4	89(3.5)		100
LPINZ-PFSSCT-12×400	400(15.75)		0.4	102(4.02)		100
LPINZ-PFSSCT-12×450	450(17.72)		0.4	115(4.53)		100
LPINZ-PFSSCT-12×500	500(19.69)		0.4	128(5.04)		100
LPINZ-PFSSCT-12×550	550(21.65)		0.4	141(5.55)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature $-40^{\circ}\text{C} \sim 850^{\circ}\text{C}$;

High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;

All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-PFSSCT-12×600	600(23.62)	12(0.472)	0.4	154(6.06)	1200(270)	100
LPINZ-PFSSCT-12×650	650(25.59)		0.4	167(6.57)		100
LPINZ-PFSSCT-12×700	700(27.56)		0.4	180(7.09)		100
LPINZ-PFSSCT-15×200	200(7.87)	15(0.59)	0.4	50(1.97)	1500(337)	100
LPINZ-PFSSCT-15×250	250(9.84)		0.4	63(2.48)		100
LPINZ-PFSSCT-15×300	300(11.8)		0.4	76(2.99)		100
LPINZ-PFSSCT-15×350	350(13.78)		0.4	89(3.51)		100
LPINZ-PFSSCT-15×400	400(15.75)		0.4	102(4.021)		100
LPINZ-PFSSCT-15×450	450(17.72)		0.4	115(4.53)		100
LPINZ-PFSSCT-15×500	500(19.69)		0.4	128(5.04)		100
LPINZ-PFSSCT-15×550	550(21.65)		0.4	141(5.55)		100
LPINZ-PFSSCT-15×600	600(23.62)		0.4	154(6.06)		100
LPINZ-PFSSCT-15×650	650(25.59)		0.4	167(6.57)		100
LPINZ-PFSSCT-15×700	700(27.56)		0.4	180(7.09)		100
LPINZ-PFSSCT-15×750	750(29.53)		0.4	191(7.52)		100
LPINZ-PFSSCT-15×800	800(31.5)		0.4	193(7.59)		100
LPINZ-PFSSCT-15×1000	1000(39.37)		0.4	206(8.11)		100
LPINZ-PFSSCT-19×800	800(31.5)	19(0.748)	0.6	223(8.781)	1500(337)	100
LPINZ-PFSSCT-19×1000	1000(39.37)		0.6	286(11.26)		100
LPINZ-PFSSCT-19×1200	1200(47.24)		0.6	350(13.78)		100
LPINZ-PFSSCT-19×1500	1500(59.04)		0.6	445(17.52)		100
LPINZ-PFSSCT-19×1800	1800(70.87)		0.6	540(21.26)		100
LPINZ-PFSSCT-19×2000	2000(78.74)		0.6	605(23.82)		100



Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-ECSSCT-4.6×200	200(7.87)	4.6(0.181)	0.4	50(1.97)	1000(225)	100
LPINZ-ECSSCT-4.6×250	250(9.84)		0.4	65(2.56)		100
LPINZ-ECSSCT-4.6×350	350(13.78)		0.4	89(3.50)		100
LPINZ-ECSSCT-4.6×550	550(21.65)		0.4	141(5.55)		100
LPINZ-ECSSCT-4.6×650	650(25.6)		0.4	165(6.50)		100
LPINZ-ECSSCT-4.6×850	850(33.46)		0.4	216(8.50)		100
LPINZ-ECSSCT-4.6×1100	1100(43.31)		0.4	280(11.02)		100
LPINZ-ECSSCT-7.9×200	200(7.87)	7.9(0.311)	0.4	50(1.97)	1200(270)	100
LPINZ-ECSSCT-7.9×250	250(9.84)		0.4	65(2.56)		100
LPINZ-ECSSCT-7.9×350	350(13.78)		0.4	89(3.50)		100
LPINZ-ECSSCT-7.9×550	550(21.65)		0.4	141(5.55)		100
LPINZ-ECSSCT-7.9×650	650(25.6)		0.4	165(6.50)		100
LPINZ-ECSSCT-7.9×850	850(33.46)		0.4	216(8.50)		100
LPINZ-ECSSCT-7.9×1100	1100(43.31)		0.4	280(11.02)		100
LPINZ-ECSSCT-7.9×150	150(5.9)	7.9(0.311)	0.4	38(1.50)	1200(270)	100
LPINZ-ECSSCT-7.9×175	175(6.89)		0.4	48(1.89)		100
LPINZ-ECSSCT-7.9×200	200(7.87)		0.4	52(2.05)		100
LPINZ-ECSSCT-7.9×240	240(9.45)		0.4	67(2.64)		100
LPINZ-ECSSCT-7.9×300	300(11.8)		0.4	82(3.23)		100
LPINZ-ECSSCT-7.9×350	350(13.78)		0.4	98(8.86)		100
LPINZ-ECSSCT-7.9×400	400(15.75)		0.4	114(4.49)		100
LPINZ-ECSSCT-7.9×450	450(17.72)		0.4	130(5.12)		100
LPINZ-ECSSCT-7.9×500	500(21.65)		0.4	146(5.75)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature -40°C ~ 850°C ;

High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;

All length are available, stainless steel type: 304, 316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-PCSSCT-5.6×100	150(5.9)	5.6(0.22)	1.2	37(1.46)	350(79)	100
LPINZ-PCSSCT-5.6×200	200(7.87)		1.2	50(1.97)		100
LPINZ-PCSSCT-5.6×250	250(9.84)		1.2	63(2.48)		100
LPINZ-PCSSCT-5.6×300	300(11.8)		1.2	76(2.99)		100
LPINZ-PCSSCT-5.6×350	350(13.78)		1.2	89(3.5)		100
LPINZ-PCSSCT-5.6×400	400(15.75)		1.2	102(4.02)		100
LPINZ-PCSSCT-5.6×450	450(17.72)		1.2	115(4.53)		100
LPINZ-PCSSCT-5.6×500	500(19.69)		1.2	128(5.04)		100
LPINZ-PCSSCT-5.6×550	550(21.65)		1.2	141(5.55)		100
LPINZ-PCSSCT-5.6×600	600(23.62)		1.2	154(6.06)		100
LPINZ-PCSSCT-5.6×650	650(25.59)		1.2	167(6.57)		100
LPINZ-PCSSCT-5.6×700	700(27.56)		1.2	180(7.09)		100
LPINZ-PCSSCT-9×150	150(5.9)	9(0.35)	1.2	50(1.97)	450(101)	100
LPINZ-PCSSCT-9×200	200(7.87)		1.2	63(2.48)		100
LPINZ-PCSSCT-9×250	250(9.84)		1.2	76(2.99)		100
LPINZ-PCSSCT-9×300	300(11.8)		1.2	89(3.5)		100
LPINZ-PCSSCT-9×350	350(13.78)		1.2	102(4.02)		100
LPINZ-PCSSCT-9×400	400(15.75)		1.2	115(4.53)		100
LPINZ-PCSSCT-9×450	450(17.72)		1.2	128(5.04)		100
LPINZ-PCSSCT-9×500	500(19.69)		1.2	141(5.55)		100
LPINZ-PCSSCT-9×550	550(21.65)		1.2	154(6.06)		100
LPINZ-PCSSCT-9×600	600(23.62)		1.2	167(6.57)		100
LPINZ-PCSSCT-9×650	650(25.59)		1.2	180(7.09)		100
LPINZ-PCSSCT-9×700	700(27.56)		1.2	191(7.52)		100

Product Features



High corrosion resistant, Multi-lock type;
Good loop tensile strength can touch 250Lbs;
Manufactured from type 304 and 316 stainless steel;
Outdoor and indoor use;
Ideal for used in telecommunication, electricity, shipbuilding and oil & industry;
Temperature: Working temperature -60°C~550°C;

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-SSCTM-7×150	150(5.9)	7(0.276)	0.25	33(1.3)	1120(252)	100
LPINZ-SSCTM-7×225	225(8.86)		0.25	57(2.2)		100
LPINZ-SSCTM-7×300	300(11.8)		0.25	81(3.2)		100
LPINZ-SSCTM-7×335	335(13.2)		0.25	92(3.6)		100
LPINZ-SSCTM-7×400	400(15.7)		0.25	113(4.4)		100
LPINZ-SSCTM-7×450	450(17.7)		0.25	129(5.1)		100
LPINZ-SSCTM-7×490	490(19.3)		0.25	141(5.6)		100
LPINZ-SSCTM-7×550	550(21.7)		0.25	161(6.3)		100
LPINZ-SSCTM-7×600	600(23.6)		0.25	176(6.9)		100
LPINZ-SSCTM-7×650	650(25.6)		0.25	192(7.6)		100
LPINZ-SSCTM-7×700	700(27.6)		0.25	208(8.2)		100
LPINZ-SSCTM-7×750	750(29.5)		0.25	224(8.8)		100
LPINZ-SSCTM-7×800	800(31.5)		0.25	240(9.4)		100
LPINZ-SSCTM-12×150	150(5.9)	12(0.472)	0.25	33(1.3)	1800(405)	100
LPINZ-SSCTM-12×225	225(8.86)		0.25	57(2.2)		100
LPINZ-SSCTM-12×300	300(11.8)		0.25	81(3.2)		100
LPINZ-SSCTM-12×335	335(13.2)		0.25	92(3.6)		100
LPINZ-SSCTM-12×400	400(15.7)		0.25	113(4.4)		100
LPINZ-SSCTM-12×450	450(17.7)		0.25	129(5.1)		100
LPINZ-SSCTM-12×490	490(19.3)		0.25	141(5.6)		100
LPINZ-SSCTM-12×550	550(21.7)		0.25	161(6.3)		100
LPINZ-SSCTM-12×600	600(23.6)		0.25	176(6.9)		100
LPINZ-SSCTM-12×650	650(25.6)		0.25	192(7.6)		100
LPINZ-SSCTM-12×700	700(27.6)		0.25	208(8.2)		100
LPINZ-SSCTM-12×750	750(29.5)		0.25	224(8.8)		100
LPINZ-SSCTM-12×800	800(31.5)		0.25	240(9.4)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;
 High tensile strength: Non-flammability;
 Temperature: Working temperature -60°C ~ 550°C ;
 High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;
 All length are available, stainless steel type:304,316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LPINZ-LSSCT-12x200	200(7.87)	12(0.47)	0.3	50(1.97)	1200(270)	100
LPINZ-LSSCT-12x250	250(9.84)		0.3	63(2.48)		100
LPINZ-LSSCT-12x300	300(11.8)		0.3	76(2.99)		100
LPINZ-LSSCT-12x350	350(13.78)		0.3	89(3.5)		100
LPINZ-LSSCT-12x400	400(15.75)		0.3	102(4.02)		100
LPINZ-LSSCT-12x450	450(17.72)		0.3	115(4.53)		100
LPINZ-LSSCT-12x500	500(19.69)		0.3	128(5.04)		100
LPINZ-LSSCT-12x550	550(21.65)		0.3	141(5.55)		100
LPINZ-LSSCT-15x250	250(9.84)	15(0.59)	0.3	63(2.48)	1500(337)	100
LPINZ-LSSCT-15x300	300(11.8)		0.3	76(2.99)		100
LPINZ-LSSCT-15x350	350(13.78)		0.3	89(3.5)		100
LPINZ-LSSCT-15x400	400(15.75)		0.3	102(4.02)		100
LSSCT-LSSCT-15x450	450(17.72)		0.3	115(4.53)		100
LSSCT-LSSCT-15x500	500(19.69)		0.3	128(5.04)		100
LSSCT-LSSCT-15x600	600(23.62)		0.3	154(6.06)		100
LSSCT-LSSCT-15x700	700(27.56)		0.3	180(7.09)		100
LSSCT-LSSCT-15x750	750(29.53)		0.3	191(7.52)		100
LSSCT-LSSCT-15x800	800(31.5)		0.3	193(7.59)		100
LSSCT-LSSCT-15x1000	1000(39.37)		0.3	206(8.11)		100
LSSCT-LSSCT-19x300	300(11.8)	19(0.748)	0.4	76(2.99)	2000(440)	100
LSSCT-LSSCT-19x400	400(15.75)		0.4	102(4.02)		100
LSSCT-LSSCT-19x500	500(19.69)		0.4	141(5.55)		100
LSSCT-LSSCT-19x600	600(23.62)		0.4	154(6.06)		100
LSSCT-LSSCT-19x700	700(27.56)		0.4	180(7.09)		100
LSSCT-LSSCT-19x800	800(31.5)		0.4	193(7.59)		100
LSSCT-LSSCT-19x900	900(36)		0.4	200(8)		100
LSSCT-LSSCT-19x1000	1000(39.37)		0.4	206(8.11)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;

High tensile strength: Non-flammability;

Temperature: Working temperature -40°C ~ 85°C ;

High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;

All length are available, stainless steel type:304,316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LSSCT-LPSSCT-12 x 150	150(5.9)	12(0.472)	0.4	37(1.46)	1200(270)	100
LSSCT-LPSSCT-12 x 200	200(7.87)		0.4	50(1.97)		100
LSSCT-LPSSCT-12 x 250	250(9.84)		0.4	63(2.48)		100
LSSCT-LPSSCT-12 x 300	300(11.8)		0.4	76(2.99)		100
LSSCT-LPSSCT-12 x 350	350(13.78)		0.4	89(3.5)		100
LSSCT-LPSSCT-12 x 400	400(15.75)		0.4	102(4.02)		100
LSSCT-LPSSCT-12 x 450	450(17.72)		0.4	115(4.53)		100
LSSCT-LPSSCT-12 x 500	500(19.69)		0.4	128(5.04)		100
LSSCT-LPSSCT-12 x 550	550(21.65)		0.4	141(5.55)		100
LSSCT-LPSSCT-12 x 600	600(23.62)		0.4	154(6.06)		100
LSSCT-LPSSCT-12 x 650	650(25.59)		0.4	167(6.57)		100
LSSCT-LPSSCT-12 x 700	700(27.56)		0.4	180(7.09)		100
LSSCT-LPSSCT-15 x 200	200(7.87)	15(0.59)	0.4	50(1.97)	1500(337)	100
LSSCT-LPSSCT-15 x 250	250(9.84)		0.4	63(2.48)		100
LSSCT-LPSSCT-15 x 300	300(11.8)		0.4	76(2.99)		100
LSSCT-LPSSCT-15 x 350	350(13.78)		0.4	89(3.5)		100
LSSCT-LPSSCT-15 x 400	400(15.75)		0.4	102(4.02)		100
LSSCT-LPSSCT-15 x 450	450(17.72)		0.4	115(4.53)		100
LSSCT-LPSSCT-15 x 500	500(19.69)		0.4	128(5.04)		100
LSSCT-LPSSCT-15 x 550	550(21.65)		0.4	141(5.55)		100
LSSCT-LPSSCT-15 x 600	600(23.62)		0.4	154(6.06)		100
LSSCT-LPSSCT-15 x 650	650(25.59)		0.4	167(6.57)		100
LSSCT-LPSSCT-15 x 700	700(27.56)		0.4	180(7.09)		100
LSSCT-LPSSCT-15 x 750	750(27.56)		0.4	191(7.52)		100
LSSCT-LPSSCT-15 x 800	800(31.5)		0.4	193(7.59)		100
LSSCT-LPSSCT-15 x 1000	1000(39.37)		0.4	206(8.11)		100

Product Features



Characteristic: They have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;
 High tensile strength: Non-flammability;
 Temperature: Working temperature -40°C ~ 85°C ;
 High resistance to acetic acid, alkali acid, sulphuric acid, corrode etc;
 All length are available, stainless steel type:304,316.

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LSSCT-LCSSCT-12 x 200	200(7.87)	12(0.51)	1.2	50(1.97)	1200(270)	100
LSSCT-LCSSCT-12 x 250	250(9.84)		1.2	63(2.48)		100
LSSCT-LCSSCT-12 x 300	300(11.8)		1.2	76(2.99)		100
LSSCT-LCSSCT-12 x 350	350(13.78)		1.2	89(3.5)		100
LSSCT-LCSSCT-12 x 400	400(15.75)		1.2	102(4.02)		100
LSSCT-LCSSCT-12 x 450	450(17.72)		1.2	115(4.53)		100
LSSCT-LCSSCT-12 x 500	500(19.69)		1.2	128(5.04)		100
LSSCT-LCSSCT-12 x 550	550(21.65)		1.2	141(5.55)		100
LSSCT-LCSSCT-12 x 600	600(23.62)		1.2	154(6.06)		100
LSSCT-LCSSCT-12 x 650	650(25.59)		1.2	167(6.57)		100
LSSCT-LCSSCT-12 x 700	700(27.56)		1.2	180(7.09)		100
LSSCT-LCSSCT-16 x 200	200(7.87)	16(0.63)	1.2	50(1.97)	1500(337)	100
LSSCT-LCSSCT-16 x 250	250(9.84)		1.2	63(2.48)		100
LSSCT-LCSSCT-16 x 300	300(11.8)		1.2	76(2.99)		100
LSSCT-LCSSCT-16 x 350	350(13.78)		1.2	89(3.5)		100
LSSCT-LCSSCT-16 x 400	400(15.75)		1.2	102(4.02)		100
LSSCT-LCSSCT-16 x 450	450(17.72)		1.2	115(4.53)		100
LSSCT-LCSSCT-16 x 500	500(19.69)		1.2	128(5.04)		100
LSSCT-LCSSCT-16 x 550	550(21.65)		1.2	141(5.55)		100
LSSCT-LCSSCT-16 x 600	600(23.62)		1.2	154(6.06)		100
LSSCT-LCSSCT-16 x 650	650(25.59)		1.2	167(6.57)		100
LSSCT-LCSSCT-16 x 700	700(27.56)		1.2	180(7.09)		100

Product Features




Made of high-strength, corrosion-resistant 304 and 316 stainless steel releasable use
Unique buckle design for quick, easy application and re-use;
Ldeal for inquiring electricity, telecommunication, shipbuliding industry;
Temperature: Working temperature -40°C~85°C;

Product Parameters

Part Number	Approx. length mm(inch)	Approx. width mm(inch)	Thickness	Max.bundle dia.mm(inch)	Min.loop tensile strength N(lbs)	Pcs/bag
LSSCT-RSSCT-6.3 × 150	150(5.9)	6.3(0.39)	0.4	33(1.3)	800(180)	100
LSSCT-RSSCT-6.3 × 190	190(7.5)		0.4	46(1.8)		100
LSSCT-RSSCT-6.3 × 250	250(9.8)		0.4	65(2.6)		100
LSSCT-RSSCT-6.3 × 300	300(11.8)		0.4	81(3.2)		100
LSSCT-RSSCT-6.3 × 350	350(13.8)		0.4	97(3.8)		100
LSSCT-RSSCT-9.5 × 400	400(15.7)	9.5(0.39)	0.4	113(4.4)	1000(225)	100
LSSCT-RSSCT-9.5 × 450	450(17.5)		0.4	129(5.1)		100
LSSCT-RSSCT-9.5 × 490	490(19.3)		0.4	141(5.6)		100
LSSCT-RSSCT-9.5 × 550	550(21.7)		0.4	161(6.3)		100
LSSCT-RSSCT-9.5 × 600	600(23.6)		0.4	176(6.9)		100
LSSCT-RSSCT-9.5 × 650	650(25.6)		0.4	192(7.6)		100
LSSCT-RSSCT-9.5 × 700	700(27.6)		0.4	208(8.2)		100

Operation Diagram



Product Features



Standard and characteristic stainless steel band clamps (cilp band, satisfaction clip) is mainly used not only for attachi cable, grounding conductors etc, but also for electrification rallway pole of telecommunicati trafficlighits and singpole, etc.

The detail is as following:

①Stainless steel band clamps is consisted of belt clamp. rartch wehhi and so on. The clamp made of high quality lmm thickness stainless steel.The belt is also made of stainless steel who width is 14mm and thickness is 0.2mm. After the two edges of the belt are hemmed, the width of belt is 10mm. The belt has strong intension and pull. The two edges of the belt are smooth.


② Stainless steel band clamps are convenient to use. The clamp is capable of easiyy atthing, detaching or tastening the belt, and it can not be liable to loosen inadvertently.

③ The length of stainless steel band clamps is in accoorance to customers requirement. At present 400mm, 600mm, 800mm, 1000mm, 1200mm,1500mm, 2000mm specifications a so on.

Product Parameters

Part Number	width		Thickness		Length		Max.bundle dia.		Pcs/bag
	inch	mm	inch	mm	inch	mm	inch	mm	
LSSCT-SSUB-10 x 400	0.4	10	0.008	0.2	15.7	400	4.3	110	100
LSSCT-SSUB-10 x 600	0.4	10	0.008	0.2	23.6	600	7.1	180	100
LSSCT-SSUB-10 x 800	0.4	10	0.008	0.2	31.5	800	9.4	240	100
LSSCT-SSUB-10 x 900	0.4	10	0.008	0.2	35.4	900	10.6	270	100
LSSCT-SSUB-10 x 1000	0.4	10	0.008	0.2	39.4	1000	11.8	300	100
LSSCT-SSUB-10 x 1100	0.4	10	0.008	0.2	43.3	1100	13.4	340	100
LSSCT-SSUB-10 x 1200	0.4	10	0.008	0.2	47.2	1200	14.6	370	100
LSSCT-SSUB-19 x 1100	0.9	19	0.008	0.2	43.3	1100	13.4	340	100
LSSCT-SSUB-19 x 1200	0.9	19	0.008	0.2	47.2	1200	14.6	370	100
LSSCT-SSUB-19 x 1300	0.9	19	0.008	0.2	51.2	1300	15.7	400	100
LSSCT-SSUB-19 x 1400	0.9	19	0.008	0.2	55.1	1400	16.9	430	100
LSSCT-SSUB-19 x 1500	0.9	19	0.008	0.2	59.0	isoa	18.1	460	100

Operation Diagram





SC-1908



HS-600



NQA



LQA



LQG

LQG STAINLESS CABLE TIES TOOL

WITH THE FUNCTION OF TENSIONING&CUTTING ETC., SUITABLE FOR SELF-LOCK STAINLESS STEEL CABLE TIES.

CABLE TIES: WIDTH:4.6MM-8MM, THICKNESS: 0.25MM-0.4MM.

HS-600 STAINLESS CABLE TIES TOOL

WITH THE FUNCTION OF TENSIONING&AUTO-SELF CUTTING ETC., SUITABLE FOR SELF-LOCK STAINLESS STEEL CABLE TIES.

CABLE TIES: WIDTH:4.6MM-8MM, THICKNESS: 0.25MM-0.4MM.

LQA STRAP BANDING TOOL

WITH THE FUNCTION OF TENSIONING&CUTTING ETC., SUITABLE FOR STRAP BANDING, SELF-LOCK STAINLESS STEEL CABLE TIES.

CABLE TIES: WIDTH:8MM-20MM, THICKNESS: 0.25MM-0.8MM.

SC-1908 HEAVY DUTY HAND-OPERATING STRAP BANDING TOOL

WITH THE FUNCTION OF TENSIONING&CUTTING ETC., SUITABLE FOR STRAP BANDING, STAINLESS STEEL CABLE TIES.

CABLE TIES: WIDTH:8MM-20MM, THICKNESS: 0.25MM-0.8MM.

Product Features




Material: Nylon 66,94v-2 certified by UL. Heat-resisting, Acid & erosion control, insulate well and not and not apt to age.

Operating temperature -40°C~85°C;

Color:Natural(or white, standard color),UV black and other colors are available as requested.

Product Parameters

Part Number	Long		Wide(mm)	Bundle diameter (mm)	Tensile strength	
	inch	mm			LBS	KGS
LSSCT-NCT-2.5 x 60	2.4"	60	2.5	2-11	18	8
LSSCT-NCT-2.5 x 80	3.2"	80	2.5	2-16	18	8
LSSCT-NCT-2.5 x 100	4.0"	100	2.5	2-22	18	8
LSSCT-NCT-2.5 x 120	4.7"	120	2.5	2-30	18	8
LSSCT-NCT-2.5 x 150	6.0"	150	2.5	2-35	18	8
LSSCT-NCT-2.5 x 160	6.3"	160	2.5	2-40	18	8
LSSCT-NCT-2.5 x 200	8.0"	200	2.5	2-50	18	8
LSSCT-NCT-3.6 x 140	5.5"	140	3.6	3-33	40	18
LSSCT-NCT-3.6 x 150	6.0"	150	3.6	3-35	40	18
LSSCT-NCT-3.6 x 180	7.1"	180	3.6	3-45	40	18
LSSCT-NCT-3.6 x 200	8.0"	200	3.6	3-50	40	18
LSSCT-NCT-3.6 x 250	10"	250	3.6	3-65	40	18
LSSCT-NCT-3.6 x 280	11"	280	3.6	3-70	40	18
LSSCT-NCT-3.6 x 300	12"	300	3.6	3-80	40	18
LSSCT-NCT-3.6 x 370	14.6"	370	3.6	3-105	40	18
LSSCT-NCT-4.8 x 120	4.7"	120	4.8	3-30	50	22
LSSCT-NCT-4.8 x 160	6.3"	160	4.8	3-40	50	22
LSSCT-NCT-4.8 x 180	7.1"	180	4.8	3-42	50	22
LSSCT-NCT-4.8 x 190	7.5"	190	4.8	3-46	50	22
LSSCT-NCT-4.8 x 200	8.0"	200	4.8	3-50	50	22
LSSCT-NCT-4.8 x 250	10"	250	4.8	3-65	50	22
LSSCT-NCT-4.8 x 280	11"	280	4.8	3-70	50	22
LSSCT-NCT-4.8 x 300	12"	300	4.8	3-80	50	22
LSSCT-NCT-4.8 x 350	14"	350	4.8	3-90	50	22
LSSCT-NCT-4.8 x 360	14.2"	360	4.8	3-94	50	22
LSSCT-NCT-4.8 x 370	14.6"	370	4.8	3-98	50	22
LSSCT-NCT-4.8 x 380	15"	380	4.8	3-102	50	22
LSSCT-NCT-4.8 x 400	16"	400	4.8	3-105	50	22
LSSCT-NCT-4.8 x 430	16.9"	430	4.8	3-120	50	22
LSSCT-NCT-4.8 x 450	17.7"	450	4.8	3-130	50	22
LSSCT-NCT-4.8 x 500	19.7"	500	4.8	3-150	50	22



Product Parameters

Part Number	Long		Wide(mm)	Bundle diameter (mm)	Tensile strength	
	inch	mm			LBS	KGS
LSSCT-NCT-7.2 × 150	6.0"	150	7.2	3-35	120	55
LSSCT-NCT-7.2 × 200	8.0"	200	7.2	3-50	120	55
LSSCT-NCT-7.2 × 250	10"	250	7.2	4-65	120	55
LSSCT-NCT-7.2 × 280	11"	280	7.2	4-78	120	55
LSSCT-NCT-7.2 × 300	12"	300	7.2	4-80	120	55
LSSCT-NCT-7.2 × 350	14"	350	7.2	4-90	120	55
LSSCT-NCT-7.2 × 370	14.6"	370	7.2	4-98	120	55
LSSCT-NCT-7.2 × 380	15"	380	7.2	4-100	120	55
LSSCT-NCT-7.2 × 400	16"	400	7.2	4-105	120	55
LSSCT-NCT-7.2 × 450	18"	450	7.2	4-110	120	55
LSSCT-NCT-7.2 × 500	20"	500	7.2	4-150	120	55
LSSCT-NCT-7.2 × 530	20.9"	530	7.2	4-160	120	55
LSSCT-NCT-7.2 × 550	21.6"	550	7.2	4-165	120	55
LSSCT-NCT-9.0 × 400	16"	400	9.0	8-105	175	79.4
LSSCT-NCT-9.0 × 450	18"	450	9.0	8-118	175	79.4
LSSCT-NCT-9.0 × 500	20"	500	9.0	8-150	175	79.4
LSSCT-NCT-9.0 × 550	21.6"	550	9.0	8-160	175	79.4
LSSCT-NCT-9.0 × 600	23.6"	600	9.0	8-170	175	79.4
LSSCT-NCT-9.0 × 650	25.6"	650	9.0	8-185	175	79.4
LSSCT-NCT-9.0 × 720	28.3"	720	9.0	10-195	175	79.4
LSSCT-NCT-9.0 × 800	31.5"	800	9.0	10-230	175	79.4
LSSCT-NCT-9.0 × 900	35.5"	900	9.0	10-265	175	79.4
LSSCT-NCT-9.0 × 1000	40"	1000	9.0	10-300	175	79.4
LSSCT-NCT-9.0 × 1100	43.3"	1100	9.0	10-335	175	79.4
LSSCT-NCT-9.0 × 1200	47.2"	1200	9.0	10-370	175	79.4
LSSCT-NCT-12 × 650	25.6"	650	12	14-185	250	114
LSSCT-NCT-12 × 900	25.5"	900	12	14-265	250	114